



High performance mono printing for demanding workgroups

Built for business, the high performance ES6150 produces professional looking documents at a fast 43ppm with the first page delivered in just 8 seconds. Productivity is further enhanced with high capacity print cartridges and large paper trays keeping down times to a minimum. Ultra efficient the ES6150 powers its way through heavy workloads making it the ideal partner for busy workgroups and mission critical environments.

Easy to integrate into busy workgroups

- Easy to share across different operating systems and software applications with PCL/PostScript emulations and networking as standard.

High performance. High quality

- Fast 43ppm mono printing meets the demands of the busiest users.
- Time to first page of just 8 seconds increases productivity.
- True 1200 x 1200dpi output ensures crisp clear image quality for consistent professional results.
- Versatile paper handling comes as standard with 2 paper trays (150 sheets and 550 sheets) to hold a variety of papers up to 216gsm.
- A maximum paper capacity of 1,800 sheets is possible through the addition of two further paper trays each of 550 sheets.
- Automatic duplex easily delivers economical, double-sided printing for a professional booklet output.

Management and control

- Once installed, the printer is simple to use, manage and control, thanks to the unique collection of utilities supplied with the printer.
- PrintSuperVision allows network administrators, to remotely monitor all printers on the network and verify toner status.
- For the security conscious Secure Print enables password-protected printing of confidential documents.

The ES6150 Mono Printers

	ES6150n	ES6150dn
Order number	01259101	01259001
Speed & throughput	A4 Print speed	43ppm
	Time to first print	8 seconds
	Printer warm up time	up to 17 seconds from power on
	Processor Speed	533MHz
Print quality	Print Resolution	1200 x 1200dpi
Typefaces	Printer fonts	99 scalable fonts PCL fonts, 1 bitmap fonts & 136 PostScript fonts
	Barcode fonts	11 types of one dimension with 28 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET
Compatibility	Connectivity	IEEE1284 Bi-directional parallel, USB 2.0, 10/100BaseTX Ethernet, 25-pin RS232C serial
	OS Compatibility ¹	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Windows Vista / Server 2003 / Server 2003 for x64; Mac OS 9.0 or greater / OS X PowerPC 10.2 or greater / OS X Intel 10.4.4 or greater
	Network & protocols	10/100Base TX Ethernet card with internal web server for printer and network card set-up and management. Includes SMTP mail client for alerts. All major network protocols supported - TCP/IP, Netware and Ethertalk. TCP/IP:- ARP, IP, ICMP, TCP, UDP, LPR, HTTP(IPP), BOOTP, WINS, DHCP, SNMP, DNS, Netware 5.x and 6 with full NDS and NDPS support: P-Server, R-Printer, EtherTalk:- ELAP, DDP, AEP, NBR, ZIP, RTMP, ATP, PAP
	Printer language	PCL6, PCL5e, PostScript 3, SIDM (Epson FX), PDF 1.3
Memory	RAM	Standard: 128MB; Maximum: 640MB
	Flash memory	12MB on board for storage of fonts, form and macros; Option up to 1GB
Utility Suite	Template Manager, PrintSuperVision, OKI LPR, PDF Print Direct ² , Network Extension, Secure Print ² , Print Control	
Paper handling	Paper capacity	Tray 1: 150 sheets of 80gsm; Tray 2: 550 sheets of 80gsm.
	Paper capacity optional paper trays	Tray 3/4: 550 sheets of 80gsm.
	Paper sizes	Tray 1: A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 76 - 215mm, Length 127 - 355mm; Envelopes: Com-10, DL, C5, Monarch; Tray 2: A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 98 - 215mm, Length 148 - 355mm; Envelopes: Com-10, DL, C5, Monarch; Tray 3/4: A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 98 - 215mm, Length 148 - 355mm; Envelopes: Com-10, DL, C5, Monarch; Duplex: A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 88 - 215mm, Length 139 - 355mm
	Paper weight	60 to 216gsm
	Optional offset catch tray	500 sheets of 80gsm
	Standard paper output	500 sheets face down, 70 sheets face up
Operating conditions	Temperature/humidity	5°C to 35°C; 15% to 85% RH non-condensing
	Storage	0°C to 35°C; 15% to 80% RH non-condensing
	Noise	Operating: Up to 56dB(A), Standby: 28dB(A), Power Save: Background Level
Power requirements	Power supply	230 VAC +/- 10%, 50 or 60Hz +/- 2%
	Power consumption	Typical 788W, Peak 1280W, Idle 95W (average), Power Save 15.3W
Dimensions (HxWxD)	404 x 422 x 465mm	404 x 422 x 549mm
Weight ³	22.9kg	24.8kg
Accessories	Duplex	○ (09004458)
	Offset catch tray	○ (09004583)
	3rd/4th Tray	○ (09004457)
	Hard Disk Drive	○ 60GB (09004630), 120GB (09004631)
	Compact Flash	○ 256MB (09004632), 512MB (09004633), 1GB (09004634)
	Memory upgrades	○ 256MB (09004628), 512MB (09004629)

● Standard ○ Optional (Order number)

¹Check local OKI Executive Series website for latest driver releases & OS Compatibility

²Hard Disk Drive required

³Approximate weight including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

Specification subject to change without notice. All trademarks acknowledged.

OKI EUROPE LTD.
Blays House, Wick Road
Egham, TW20 0HJ
United Kingdom
T +44(0) 20 8219 2190
F +44(0) 20 8219 2199
WWW.OKIEXECUTIVESERIES.COM



OKI
PRINTING SOLUTIONS